

## LIBRA - Technical specifications

Motor	(A43) European (A46) UK (A44) USA	230V/50Hz - 1.5 hp 240V/50Hz - 1.5 hp 115V/60Hz - 1.5 hp
Drum width	Expansion / Classic	200 mm - 8"
	Rent	200 mm - 8"
Drum diameter	Expansion / Classic	151 mm - 6"
	Rent	151 mm - 6"
Abrasive size	Expansion	Ring shaped 203 x 480 mm - 8" x 19"
	Classic	203 x 550 mm - 8" x 21.6"
	Rent	203 x 470 mm - 8" x 18.5"
Drum speed	Expansion	3000 rpm
	Classic/Rent	2500 rpm
Handles		Adjustable in height (2 posizioni)
Control lever		On the handle
Level control		Cam on wheel
Motor protection		"Dead man" lever; when lever is released the motor stops
Wheels		Ø64 mm adjustable
Bearings		Permanent lube radial ball
Drum pressure adjustment		Infinite positions
Noise (acoustic pressure level weighted and measured at 0.4 m from grip and 1.5 m from floor level)		91.5 db(A)
Vibrazione (valore ponderato dello scarto quadratico medio dell' accelerazione)		$\leq 1.98 \text{ m/s}^2$
Machine overall dimensions		320 x 600 x 960 mm
Net weight		47 kg - 104 lbs
Package dimensions		2 colli 660 x 370 x 640 mm e 340 x 220 x 880 mm
Gross weight		54 kg - 119 lbs
Standard equipment		Dust bag, plug, spanner, use and maintenance handbook