

RT ASINCRONOUS - Technical specifications

Motor	RT 17" 1.5 hp	230V/50Hz - 1.5 hp 220V/60Hz - 1.5 hp 115V/60Hz - 1.5 hp
	RT 17" 1.8 hp	230V/50Hz - 1.8 hp
	RT 17" 2.0 hp S	230V/50Hz - 2.0 hp 220V/60Hz - 2.0 hp
	RT 17" 2.5 hp ES	230V/50Hz - 2.5 hp 220V/60Hz - 2.5 hp
	RT 17" 2.5 hp EH	230V/50Hz - 2.5 hp 220V/60Hz - 2.5 hp
	RT 17" 4.0 hp BF	230V/50Hz - 4.0 hp 220V/60Hz - 4.0 hp
	Disk diameter	
Disk speed	RT 17" 1.5 hp	140 rpm
	RT 17" 1.8 hp	140 rpm
	RT 17" 2.0 hp S	140 rpm
	RT 17" 2.5 hp ES	140 rpm
	RT 17" 2.5 hp EH	240 rpm
	RT 17" 4.0 hp BF	140 rpm
Handle		Adjustable in 3 positions
Control lever		On the handle
Motor protection		Double protection: the machines stops with the handle in vertical position and the machine stops when the control lever is released.
Wheels		Ø 125 mm replaceable
Reduction gear		Steel gears - Dipped in oil
Noise (acoustic pressure level weighted and measured at 0.4 m from grip and 1.5 m from floor level)		80 db(A)
Vibration (weighted value of root mean square acceleration)		$\leq 1.45 \text{ m/s}^2$
Machine overall dimensions		455 x 660 x 110
Net weight		48-51 kg 106-112 lbs
Package dimensions		2 boxes 590 x 435 x 340 mm and 460 x 200 x 1025 mm
Gross weight		51- 54 kg 112-119 lbs
Standard equipment		Use and maintenance handbook