

TAURUS / NT8 - Technical specifications

Motor	(A34) European (A50) European (A35) USA (A35-5Hp) USA	230V/50Hz - 4 hp 400V3/50Hz - 4 hp 220V/60Hz - 4 hp 220V/60Hz - 5hp
Drum width		200 mm - 8"
Drum diameter		185 mm - 7" 1/4
Sanding paper size		203 x 750 mm - 8" x 29 1/2"
Drum speed	a 50 Hz a 60 Hz	1800/2050 rpm 2000/2250 rpm
Control lever		On handle
Level control		Cam on wheel
Motor protection		After power failure the motor does not restart automatically
Wheels		Ø 112 e 87 mm replaceable
Bearings		Permanent lube radial ball
Drum pressure adjustment		Infinite positions
Noise (acoustic pressure level weighted and measured at 0.4 m from grip and 1.5 m from floor level)		87,5 db(A)
Vibration (weighted value of root mean square acceleration)		<= 1.11 m/s ²
Machine overall dimensions		1045 x 382 x 980 mm
Net weight		85 kg - 187 lbs
Package dimensions		760 x 536 x 830 mm
Gross weight		95 kg - 210 lbs
Standard equipment		Dust bag, plug, spanner, use and maintenance handbook